

A REVIEW ON DYNAMIC WIND ANALYSIS OF TALL BUILDING PROVIDED WITH STEEL BRACING AS PER PROPOSED DRAFT FOR INDIAN WIND CODE AND EFFECT OF SOFT STOREY

Ashwini S Gudur¹ Prof. H S Vidyadhar²

¹ PG Student ² Associate Professor

^{1,2}Department of Civil Engineering

^{1,2}P. D. A. C. E Gulbarga-585103

ABSTRACT- For preliminary design including the proportioning of a structure, the variation of wind force on a structure with variation of site parameters and structural parameters should be known. The present study is an effort to achieve the same, primarily based on proposed draft for Indian wind code considering two different wind speed zones. RC framed buildings are generally designed without considering the structural action of masonry infill walls present. These walls are widely used as partitions and considered as non-structure elements. But they affect both structural and non-structural performance of the RC buildings with lateral loads.

KEYWORDS: proposed draft code, Indian wind code, Soft storey, Equivalent diagonal strut, Dynamic coefficient factor, Displacement, drift.

I. INTRODUCTION

A. General

Codes and standards are the mainstream of information to the designers of civil engineering structure. The wind loading codes are primarily based on comprehensive data on wind speeds collected by the meteorological departments, and the results of the results of the research carried out understand wind characteristics and its effect on structure, based on these data and experiments made in wind tunnel.

As wind is a randomly varying dynamic phenomenon, it has significant dynamic effects on buildings and structures especially on high rise flexible structures. Codes and standards utilize the "gust loading factor" (GLF) approach for estimating dynamic effect on high-rise structures. The concept of GLF was first introduced by davenport in 1967. Wind is air in motion relative to the surface of earth. The effect of wind on the structure as a whole is determined by the combined action of external & internal pressures acting upon it. Wind velocity consists of a mean plus a fluctuating component,

momentary deviation of the fluctuating component from the mean value is responsible for creation of gust. Both the components of wind velocity vary with height & depend upon the approach terrain & topography.

II. METHODOLOGY

The design wind velocity (V_z) is given by

$$V_z = V_b \cdot K_1 \cdot K_2 \cdot K_3$$

The design wind pressure (P_a) is given by

$$P_z = 0.6V_z^2$$

Where V_b = basic wind speed as per IS 875: PART -3, V_z is design wind pressure at height z in m/s, k_1 is the probability factor given in IS 875 part 3 table 1, k_2 is the terrain roughness and height factor given in table 2, k_3 is topographical factor and k_4 is cyclonic factor.

DYNAMIC RESPONSE FACTOR: According dynamic response factor as per proposed wind code method the following equations are used.

Where P_z = Design wind pressure at height z in N/m^2 given by

$$C_{dyn} i$$

i s dynamic response factor (total load / mean load) and is given by

$$C_{dyn} = \frac{1 + 2 \cdot I_h [g v^2 \cdot b s + \frac{H_s g r^2 S E]^{0.5}}{\beta}}{(1 + 2 g v I_h)}$$

Where I_h = turbulence intensity, obtained from table 31 of IS: 875 (part 3): proposed draft and commentary; $g v$ = peak factor for the up wind velocity fluctuations, which shall be taken as

Bs is back ground factor, which is a measure of the slowly varying background component of the fluctuating response, caused by the low frequency wind speed variations given as follows.

$$B_s = \frac{1}{1 + \frac{[36(h-s)^2 + 64b^2sh]^{0.5}}{2Lh}}$$

S is size reduction factor given by expression presented below

$$S = \frac{1}{\left[1 + \frac{4foh(1+gvIh)}{Vh}\right] \left[1 + \frac{4foboh(1+gvIh)}{Vh}\right]}$$

E is $\left(\frac{\pi}{4}\right)$ times the spectrum of turbulence in the approaching wind stream given by

$$E = \pi N / (1 + 70N^2)^{5/6}$$

And N = reduced frequency, and is given by

$$N = \frac{fo Lh [1+(gv+Ih)]}{Vh}$$

Where Vh = design wind speed at height h.

III. DESCRIPTION OF STRUCTURAL MODEL

Twenty five storey building is considered having 8 bays in X and Y directions with plan dimension 40x40m and storey height 3.5m each in all the floors and spacing is 5m. the building is kept symmetric in both mutually perpendicular directions in plan to avoid torsional effects. The orientation and size of column is kept same throughout the height of the structure. The building is considered for wind speed zones 47 m/s and the response obtained. The building is considered as general building located in terrain category three i.e. has obstruction up to 10m height of building and surface is plain.

Data	Values
Basic wind speed V_b	47 m/s
E for M30 concrete	27.386X10 ⁶ KN/m ²
E of brick masonry	3500X10 ³ KN/m ²
Density of brick masonry	20 KN/m ³
Density of reinforced concrete	25 KN/m ³
Grade of concrete	M30
Loads	
Floor finishes	1 KN/m ²
Imposed load	3 KN/m ²
Slab thickness	0.15m


Column size	0.23mX0.7m
Beam size	0.23mX0.45m
Thickness of wall	0.23m

Table 1: Description of structural model


IV. MODELS FOR ANALYSIS

Following six models are analyzed as special moment resisting frame using equivalent static analysis and dynamic response spectrum analysis.


- Model 1: Bare frame model without bracings, however masses of infill walls are included in the model.
- Model 2: Bare frame model with V bracings.
- Model 3: Full Infill model without bracings.
- Model 4: Full Infill model with V bracings.
- Model 5: building has one full brick Infill masonry wall in all storeys without bracing with ground soft storey.
- Model 6: building has one full brick Infill masonry wall in all storeys with V bracing with ground soft storey.




Model 1




Model 2




Model



Model 3



Model 4



Model 5

V. RESULT AND DISCUSSION

Table 2: Lateral displacement and storey drifts for bare frame model with V bracing for wind speed zones 47 m/s.

STORY NO	DISP X	DISP Y	DRIFT X	DRIFT Y
26	35.66	35.66	0.0000	0.0000
25	35.33	35.33	0.0001	0.0001
24	34.92	34.92	0.0001	0.0001
23	34.41	34.41	0.0001	0.0001
22	33.79	33.79	0.0002	0.0002
21	33.06	33.06	0.0002	0.0002
20	32.22	32.22	0.0002	0.0002
19	31.27	31.27	0.0003	0.0003
18	30.22	30.22	0.0003	0.0003
17	29.06	29.06	0.0003	0.0003
16	27.81	27.81	0.0003	0.0003
15	26.45	26.45	0.0004	0.0004
14	25.00	25.00	0.0004	0.0004
13	23.46	23.46	0.0004	0.0004
12	21.83	21.83	0.0004	0.0004

		3	9	9
11	20.11	20.11	0.0005	0.0005
		1	1	1
10	18.32	18.32	0.0005	0.0005
		2	3	3
09	16.44	16.44	0.0005	0.0005
		4	5	5
08	14.50	14.50	0.0005	0.0005
		0	7	7
07	12.49	12.49	0.0005	0.0005
		9	9	9
06	10.42	10.42	0.0006	0.0006
		2	0	0
05	8.303	8.303	0.0006	0.0006
		3	1	1
04	6.152	6.152	0.0006	0.0006
		2	1	1
03	4.007	4.007	0.0005	0.0005
		7	8	8
02	1.970	1.970	0.0004	0.0004
		0	4	4
01	0.424	0.424	0.0002	0.0002
		5	1	1

15	2.2587	2.1245	0.000042	0.000039
14	2.1100	1.9865	0.000043	0.000040
13	1.9582	1.8453	0.000044	0.000041
12	1.8038	1.7013	0.000045	0.000042
11	1.6474	1.5550	0.000045	0.000042
10	1.4894	1.4070	0.000045	0.000043
09	1.3306	1.2579	0.000045	0.000043
08	1.1716	1.1083	0.000045	0.000043
07	1.0131	0.9589	0.000045	0.000042
06	0.8560	0.8106	0.000044	0.000042
05	0.7010	0.6642	0.000043	0.000041
04	0.5493	0.5206	0.000042	0.000040
03	0.4017	0.3809	0.000040	0.000038
02	0.2604	0.2469	0.000045	0.000043
01	0.1012	0.0959	0.000051	0.000048

Table 3: Lateral displacement and storey drifts for infilled frame model for V bracing wind speed zone 47 m/s.

STORE Y NO	DISP X	DISP Y	DRIFT X	DRIFT Y
26	3.5866	3.3267	0.000027	0.000023
25	3.4933	3.2450	0.000028	0.000025
24	3.3943	3.1578	0.000030	0.000027
23	3.2895	3.0646	0.000032	0.000028
22	3.1788	2.9656	0.000033	0.000030
21	3.0625	2.8608	0.000035	0.000032
20	2.9407	2.7505	0.000036	0.000033
19	2.8136	2.6349	0.000038	0.000034
18	2.6816	2.5142	0.000039	0.000036
17	2.5449	2.3887	0.000040	0.000037
16	2.4038	2.2586	0.000041	0.000038




Fig 1: Comparison of Lateral displacement Vs Storey No for bare frame model for wind speed zone 47m/s.




Fig 2: Comparison of Lateral displacement Vs Storey No for infilled frame model for wind speed zone 47m/s.




Fig 4: Comparison of Drift Vs Storey No for bare frame model for wind speed zone 47m/s.




Fig 3: Comparison of Drift Vs Storey No for bare frame model for wind speed zone 47m/s.

VI. CONCLUSIONS

- 1) Dynamic coefficient factor not only varies with the height of the structure but is also influenced by wind speed zones.
- 2) Dynamic wind load increases with increase in height of structure
- 3) Dimension of the column should be increased to increase the lateral resistance.
- 4) Infill model effectively braces the RC frame structure and increases the lateral resistance to wind loads. Hence the effect of infill has to taken in consideration during the design of structure.
- 5) Wind forces remains constant up to 3 stories and increases linearly over the height of the building for wind speed zones 47m/s
- 6) Effect of soft storey increases with increase in position of soft storey as the lateral resistance goes on decreases.
- 7) Displacements limits are exceeding wind speed zones for bare framed model. Though practically such system do not exit it is very vulnerable.
- 8) Maximum displacements are within the limits for wind speed zones for infilled model and displacement decreased by 77.84% compared with displacements of bare frame model indicates the huge increase in lateral resisting system by considering the effect of infill.
- 9) Maximum displacement exceeded limits for model 1 3, model 1 4, model 15 in Y direction for 47 m/s wind speed zones maximum displacement

in either direction were within limits. This clearly suggests that the influence of soft stories is predominant in 47 m/s wind speed zone and hence the lateral stiffness has to be increased.

- 10) .Maximum storey drift is found a ground stories for model 1 3, model 1 4, model 1 5and abrupt increase in drifts were found for soft stories indicating large decrease in stiffness. So the stiffness has to be increased by provision of infill, increasing dimension of column or by some other lateral resisting system to increase the lateral resistance against wind loads and reduce soft storey effects.
- 11) Soft storey exhibits very poor performance in case of 47 m/s wind speed zones.

REFERENCES

- [1] "Wind analysis of building frames on sloping ground" by Umakant Arya, Aslam Hussain, Waseem Khan
- [2] "The effect of zone factors on wind and earthquake loads of high rise structures" by Dr. K. R. C. reddy and sandip A. Tupat.
- [3] "Wind behavior of buildings with and without shear wall" by Alfa Rasikan, M G Rajendran.
- [4] "Wind effects on tall building frames" by B. Dean Kumar and B.L.P Swami.
- [5]. "Effects of wind pressure on R.C tall buildings using gust factor method" by Ranjitha, K. P. Khalid Nayaz khan.
- [6] "Effects of wind load on the aspect ratio of the building" by Chandradhara G. P, Vikram M. B.
- [7] "Wind effects on multi-stored buildings: a critical review of Indian codal provisions with special reference to American standard" by Halder L. and S. C. Dutta.
- [8] "Behaviour of multistoried building under effect of wind load "by Swati D Ambadkar and Vipul S Bawar.
- [9] "Wind analysis and design of multi bay multi storey 3d RC frame" Jawad Ahmed and H S Vidyadhar.
- [10] "Static analysis of masonry infilled RC frame with & without opening including soft storey of symmetric building" by Nikhil S. Agrawal, Prof.P.B Kulkarni.
- [11] A project on "Sesmic Evolution of RC frame buildings with influence of masonry infill panel" by Md irfanullah and Vishwanth. B. patil.
- [12] IS:875 (Part) - 1987, Indian standard code of practice for design loads (other than earthquake)

for buildings and structures, part 3 wind loads, bureau of Indian standards, new Delhi, India.

- [13] IS: 875 (Part 3): Wind loads on buildings and structures - proposed draft & commentary, document No.:IITK - GSDMA-Wind 02-V 5.0.
- [14] A project on "Sesmic Evolution of RC frame buildings with influence of masonry infill panel" by Md irfanullah and Vishwanth. B. patil.
- [15] Subramanian N. (2008), "Design of Steel Structures" oxford university press, new-delli, india.[16] Nikhil S. Agrawal, Prof.P.BKulkarni " static analysis of masonry infilled RC frame with & without opening including soft storey of symmetric building"". International journal of scientific and research publications, volume 3, issue 9, sept 2013.

- [17] Bhola M. Sontakke, Ashish S Moon " Seismic behavior of soft storey RC building during earthquake" international journal on recent and innovation trends in computing and communication, volume: 3 issue 2, ISSN: 2321-8169.

- [18] CEB (1996), RC Frames under Earthquake Loading - state of the art report, Comite Euro-International Du Beton, Thomas Telford, UK.

- [19] Earthquake resistant design of structure book (2006) by PankajAgrawal.

- [20] Subramanian N. (2008), "Design of steel structures "Oxford University press, New-Delhi, India.